



## Display/Operation

Function indicator	yes
Power indicator	no

## Electrical connection

Connection	M8x1 connector, 3-pin
Polarity reversal protected	yes
Protection against device mix-ups	yes
Short-circuit protection	yes

## Electrical data

Load capacitance max. at Ue	0.5 µF
No-load current I <sub>o</sub> max., damped	9 mA
No-load current I <sub>o</sub> max., undamped	3 mA
Operating voltage U <sub>b</sub>	10...30 VDC
Output resistance R <sub>a</sub>	33.0 kOhm + D
Rated insulation voltage U <sub>i</sub>	250 V AC
Rated operating current I <sub>e</sub>	200 mA
Rated operating voltage U <sub>e</sub> DC	24 V
Rated short circuit current	100 A
Ready delay t <sub>v</sub> max.	20 ms
Residual current I <sub>r</sub> max.	20 µA
Ripple max. (% of U <sub>e</sub> )	15 %
Switching frequency	700 Hz
Utilization category	DC -13
Voltage drop static max.	2.5 V

## Environmental conditions

Ambient temperature	-25...70 °C
Contamination scale	3
EN 60068-2-27, Shock	Half-sinus, 30 gn, 11 ms

EN 60068-2-6, Vibration	55 Hz, amplitude 1 mm, 3x30 min
IP rating	IP67

## Functional safety

MTTF (40 °C)	830 a
--------------	-------

## General data

Approval/Conformity	cULus CE EAC
Basic standard	IEC 60947-5-2
Trademark	Global

## Material

Housing material	Stainless steel
Material sensing surface	PBT

## Mechanical data

Dimension	Ø 8 x 40 mm
Installation	for flush mounting
Size	M8x1
Tightening torque	8 Nm

## Output/Interface

Switching output	PNP normally open (NO)
------------------	------------------------

## Range/Distance

Assured operating distance S <sub>ao</sub>	1.6 mm
Hysteresis H max. (% of S <sub>r</sub> )	15.0 %
Rated operating distance S <sub>n</sub>	2 mm

Real switching distance sr	2 mm
Repeat accuracy max. (% of Sr)	5.0 %
Switching distance marking	■ ■
Temperature drift max. (% of Sr)	10 %
Tolerance Sr	±10 %

### Remarks

The sensor is functional again after the overload has been eliminated.  
 With connector, e.g. BKS-S 49-... total length = switch length + 12 mm.

For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

### Connector view



### Wiring Diagram

